

master view™ max

Slideaway LCD KVM Switch

Diagram

Model: **CL-1208**
CL-1216

Features

- Integrated KVM console featuring a 15" or 17" LCD monitor in 1U high rack mountable Slideaway housing
- Slideaway™ housing is specifically designed with clearance - top and bottom - for smooth operation in a 1U high system rack
- Dual consoles
- Improved design-Single person installation (Optional)
- Daisy chain up to 31 additional CS-1216A units and control up to 512 computers
- Less than 1U high mountable rack
- Port selection via Pushbutton, Hotkey and OSD
- Two level password security - only authorized user view and control the computers - up to four users plus an administrator with separate profiles for each
- DDC emulation of the LCD monitor - VGA settings of every connected computer are automatically adjusted for optimal output to the LCD monitor

Specifications

| Function | | CL-1208 | CL-1216 |
|----------------------------|-------------|---|-----------------------|
| Computer Connections | Direct | 8 | 16 |
| | Max | 256 (via Daisy Chain) | 512 (via Daisy Chain) |
| Port Selection | | Push button switches; OSD (On Screen Display); Hotkeys | |
| LEDs | On Line | 8 (Orange) | 16 (Orange) |
| | Selected | 8 (Green) | 16 (Green) |
| | Power | 1 (Blue) | |
| | Lock | 1 x Num Lock (Green) 1 x Caps Lock (Green) 1 x Scroll (Green) | |
| Connectors | CPU Ports | 8 x SPHD-15 F | 16 x SPHD-15 F |
| | Daisy Chain | 1 x DB-25 M | |
| | FW Upgr. | 1 x RJ-11 | |
| Switches | | 1 x Slide (FW Upgrade Recovery) | |
| Scan Interval (OSD Select) | | User Specified: 1 - 255 secs. | |
| Emulation | Keyboard | PS/2 | |
| | Mouse | PS/2 | |
| Video | | 15" LCD: 1024 x 768; DDC2B 17" LCD: 1280 x 1024; DDC2B | |
| Power Consumption | | 120V 60Hz 24W / 230V 50Hz 24W | |
| Operating Temperature | | 0 - 50° C | |
| Storage Temperature | | -20 - 60° C | |
| Humidity | | 0 - 80% RH | |
| Housing | | Metal | |
| Weight | 15" LCD: | 13.4kg | 15" LCD: 14.3kg |
| | 17" LCD: | 13.8kg | 17" LCD: 14.5 |