

VC810

HDMI to VGA Adapter



Installation

1. Connect one end of your VGA cable to your VGA-enabled display device.
2. Connect the other end of the VGA cable to the VC810's VGA port.

VC810

HDMI 轉 VGA 視訊轉換器



硬體安裝

1. 將VGA線材連接到VGA顯示裝置
2. 將 VGA 線材的另一端，連接至 VC810 的 VGA

BSMI



D33866
RoHS

設備名稱：HDMI 轉 VGA 視訊轉換器 Equipment name				型號（型式）：VC810 Type designation (Type)		
單元 Unit	限用物質及其化學符號 Restricted substances and its chemical symbols					
	鉛 Lead (Pb)	汞 Mercury (Hg)	鎘 Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr ⁺⁶)	多溴聯苯 Polybrominated biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
印刷電路部 件 PCBA	—	○	○	○	○	○
塑膠/其他 部件 Plastic /Others parts	○	○	○	○	○	○
金屬部件 Metal parts	—	○	○	○	○	○
備考 1. “超出 0.1 wt %” 及 “超出 0.01 wt %” 係指限用物質之百分比含量超出百分比含量基準值。 Note 1 : “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition. 備考 2. “○” 係指該項限用物質之百分比含量未超出百分比含量基準值。 Note 2 : “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence. 備考 3. “—” 係指該項限用物質為排除項目。 Note 3 : The “—” indicates that the restricted substance corresponds to the exemption.						

代理商：宏正自動科技股份有限公司

地址：新北市汐止區大同路二段 125 號三樓

- 最大額定電壓: 3.3Vdc, 0.5A

- 最大操作環境溫度: 60°C



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrators, Inc.